



EN 16510
BlmSchV Stufe 2
Regensburger BStV / Aachener BStV / Munchener BStV
ART.15a B-VG / Klimafonds / LRV
4 stelle DM.186 / Conto Termico 2.0



(Max) nominal heat output	6.3 kW
Minimum heat output	2.5 kW
Efficiency at Max	91.5 %
Efficiency at Min	92 %
Energy Efficiency Class (A++ / G scale)	A+
Energy Efficiency Index (EEI)	122 %
Seasonal space heating energy efficiency (ηs)	81 %
Temperature of exhaust smoke at Max	198 °C ***
Temperature of exhaust smoke at Min	124 °C ***
PM / OGC / NOx at Max (13% O2)	17 / 1 / 139 mg/Nm3
PM / OGC / NOx at Min (13% O2)	27 / 2 / 131 mg/Nm3
CO at 13% O₂ at Min and at Max	0.055 / 0.007 %
CO₂ at Min and at Max	7.4 / 12.8 %
Recommended draught at Max power	10 Pa ****
Minimum draught allowed for minimum power	5 Pa ****
Mass of smoke at Min and at Max	2.5 / 3.7 g/sec
Hopper capacity	24 l / 16 kg *
Fuel dimensions	Ø6mm L3÷40mm
Hourly consumption at Min and at Max	0.6 / 1.45 kg/h *
Autonomy at Min and at Max	26 / 11 h *
Heatable volume m3	115 / 180 / 315 **
Combustion air inlet	Ø 50 mm
Air inlet	80 cm2
Smoke outlet	Ø 80 mm
Nominal electrical power (EN 60335-1).	49 W (max 380 W)
Supply voltage and frequency	230 Volt / 50 Hz
Net weight	90 kg
Distance from combustible material (back/side/under)	50 / 100 / 0 mm
Distance from combustible material (front/ceiling)	800 / 1000 mm

* Data that may vary depending on the type of pellets used.

**Heatable volume based on the requested power per m3 (respectively 55-35-20 W/m3)

*** Flue gas temperature at the appliance outlet, to be used in the chimney sizing calculation (according to EN 13384-1)

**** Consider a minimum draught of 2 Pa in the EN 13384-1 chimney dimensioning calculations